

Email: <a href="mailto:enquiries@instagroup.co.uk">enquiries@instagroup.co.uk</a> Web: <a href="mailto:www.instacoustic.co.uk">www.instacoustic.co.uk</a>

# Flooring Systems IN19

## **Product References IN19**

Clause Reference: K11 - Sections 225, 275, 295

Shallow floating floor overlay system for impact sound insulation of concrete substrates in new buildings or refurbishment/material change of use projects where a level floor is present. Primarily for concrete floors.

Comprises Tongue and Groove TG4 chipboard and resilient decoupling fibre.

- For loose laying over level substrates, prior to installation of final floor covering.
- Thin System, suitable where floor to ceiling heights are restricted.
- Can be laid to new or existing skirtings.
- Suitable for where floor to ceiling height restrictions are a concern.
- Also suitable for timber floors.
- System thickness 29mm: System weight 15kg/m²

### **Substrates:**

- Requires substrate level to ≤3mm over a 3m run. Tolerances outside this limit require InstaCoustic levelling system with cradles and timber battens such as C40.
- Precast floors to be fully grouted.
- Screeds to be fully cured before installation.
- Seal all perimeters and sub-floor joints.



Email: <a href="mailto:enquiries@instagroup.co.uk">enquiries@instagroup.co.uk</a> Web: <a href="mailto:www.instacoustic.co.uk">www.instacoustic.co.uk</a>

# Flooring Systems IN19

## **Product References IN19**

Clause Reference: K11 - Sections 225, 275, 295

### Installation

- Lay resilient decoupling fibre on floor ensuring entire structural floor area is covered.
- Leave no gaps at perimeter between skirting or walls.
- Fit overlay boards at right angles to direction of decoupling fibre.
- Overlay boards to be laid with staggered joint formation.
- Glue all board joints with InstaCoustic Adhesive Plus as laying proceeds.

#### Finishes:

 Suitable to receive applied finishes (consult product manufacturer). Vinyl coverings may not conceal board joints and may require supplementary overlay of hardboard or plywood (consult vinyl supplier)

### **Guidance**

As standard

Overlay Board: 18mm Tongue and Groove TG4 Chipboard 2400 x 600mm

**IN5 Decoupling Fibre:** 1000mm x 11mm x 20m roll.

### **Further Information:**

Manufacturer: InstaGroup Ltd

Web: www.instagroup.co.uk/acoustic-systems

Telephone: 0118 932 8811

Email: enquiries@instagroup.co.uk

IN19 Technical Specification Clauses Version: 2 Version date: 31 October 2022 Page 2 of 2